

DVR4TH250*	4 Channel Hybrid Pentaplex H.264 DVR
DVR8TH250*	8 Channel Hybrid Pentaplex H.264 DVR
DVR16TH250*	16 Channel Hybrid Pentaplex H.264 DVR

*Standard DVR comes with a 250GB HDD - other configurations available up to 3TB internal**

Available with per camera
Digital Deterrent™



Audio For Security or Retail Applications

Features

- Free Speco DDNS server for use with dynamic IP addresses
- MAC™ & PC compatible software included
- Hybrid Operation: Up to 4 channels with popular protocols supported including Speco, SIP, ACTi, Axis, Sony, Vivotek, Hunt, Sanyo & others
- Selectable H.264, MPEG4, or MJPEG compression
- POS/ATM support with text overlay and searchable database
- Pentaplex operation enabling simultaneous live view or playback while continuing to record, network transfer
- Remote monitoring, recording, playback, change system settings and dome camera control via network and/or internet
- Jog shuttle for easy operation
- Real Time live display
- Remote control included - individually control up to 16 DVRs
- Rack ears included
- Recording rate up to 480 fps
- 4/8/16 channels of audio input
- 3/7/15 channels of 2-way audio
- Supports 3 Sata HDDs
- Digital output via HDMI cable
- DVD/RW Standard for video clip exporting
- USB 2.0 port for video clip exporting, supports USB ThumbDrive®
- Easy software upgrade via Network, USB ThumbDrive®, or CD/DVD
- Configurable per channel normal and event recording frame rate & picture quality or globally via EZ record
- Free Central Management System (CMS) software allows viewing of 256 simultaneous channels on a PC
- Email notification of alarm events
- Per channel built-in dome camera protocol (through RS485) including Pelco D, Pelco P, Panasonic, Panasonic C, AD422, Fastrax, JVC
- Automatic camera detection (Plug & Play)
- Digital Zoom 2 x 2 in live mode and playback
- Covert camera operation provides enhanced security, administrator control
- Dynamically programmable recording priority, motion detection, alarms and scheduling
- Programmable call-monitor switching sequence

**4TB maximum if DVD-RW is removed



Remote & Rack Ears Included

- Auto reboot feature: on/off
- Up to 30 second pre-alarm recording
- USB mouse and keyboard supported
- Multiple language on-screen menus
- Password to secure installation with 8 configurable user authentication levels
- Network software supports static IP, DHCP, PPPoE & DDNS
- Network hardware supports 10/100/1000 NIC
- Dimensions: 4 7/8" H X 17 1/4" W X 16 3/4" D
- Weight: 18.45 lbs. with 1 HDD (HDD weighs 1 lb.)
- Power Consumption: Start up @ 90W, Running @ 60W
- HDD size: 250GB, 1TB, 2TB and 3TB configurations**
- Operating temperature: 14° F to 120° F
- UL Listed
- 3 year warranty

Speco Technologies is constantly developing product improvements.

We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Rev. 11/18/09

For more information contact Speco Technologies

200 New Highway, Amityville, NY 11701 • Toll Free: 1-800-645-5516 • Fax: 631-957-9142 or 631-957-3880

www.specotech.com

Technical Specifications:
4, 8 or 16 Channel H.264 Hybrid
Pentaplex Digital Video Recorders



MODEL NAME			DVR4TH250	DVR8TH250	DVR16TH250	
Video	Operation System		Embedded (Linux)			
	Video Standard		NTSC / PAL switch selectable			
	Video Operation		Pentaplex+ (Live, Record, Playback, Remote, and Internet access)			
	Resolution – Live Video		NTSC: 720 x 480 pixels PAL: 720 x 576 pixels			
	Input		BNC x 4, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 8, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 16, BNC x 1 1.0Vp-p / 75 Ohm	
	Outputs	Main Monitor		VGA x 1, BNC x 1, S-Video x 1, 1.0Vp-p / 75 Ohm		
		Call Monitor		BNC x 1 1.0Vp-p / 75 Ohm		
		Looping		BNC x 4, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 8, BNC x 1 1.0Vp-p / 75 Ohm	BNC x 16, BNC x 1 1.0Vp-p / 75 Ohm
	VGA Output		800 x 600, 1024 x 768, 1280 x 1024 pixels @ 60Hz, 75Hz			
	Digital Output		Via HDMI cable			
	Picture Refresh Rate (Live View)		NTSC: 480 PPS (16 CH) / PAL: 400 PPS (16 CH)			
Digital Zoom (Live & Playback)		2 x 2				
Camera Installation		Plug & Play				
Audio	Input		4, Line-In	8, Line-In	16, Line-In	
	Main Output		RCA x 1, Line-Out			
	Output		4, Line-Out	8, Line-Out	16, Line-Out	
	2-Way Audio		3/7/15 Channels Supported			
	Recording Mode		Always Real Time Record, Synchronized w/ Video			
	Compression Method		ADPCM, G.726			
	File Size		8KB / Sec.			
	Operation		Local and Remote			
Playback		Only for Video Original Speed				
Recording	Compression Method		H.264 / MPEG4 / MJPEG			
	Recording Mode		Schedule, Alarm, Motion Detection			
	Pre-Alarm		0~30 Sec.			
	Resolution & Rate	NTSC	720x480:	60 fps		
			720x240:	120 fps		
			352x240:	240 fps		
	Recording Quality		8 levels presets, adjustable			
Image Size		2K to 24K Byte / picture				
Storage Mode		Linear / Circular				
Playback	Playback		Play, Stop, Pause, Rewind, Forward, Search			
	Playback Speed Adjustment		Yes 1X, 2X...32X			
	Retrieve		Date / Time, Event Playback			
	Data Life Time		Yes (Programmable)			
Storage	Built-in Storage		X4 SATA, HDD / DVD+RW			
	Built-in HDD		Up to 3 built-in HDDs (3TB max.)			
	External Storage		USB HDD			
	Export		USB 2.0 ports, X4, supports ThumbDrive®, DVD+RW			
Alarm	Alarm Input		X4, Terminal Block	X8, Terminal Block	X16, Terminal Block	
	Alarm Detection		N.C. / N.O., Programmable			
	Auditory Alert		Built-in Buzzer			
	Motion Detection		15 X 11 Grid Array, Sensitivity, Trig Level Adjustable			
	Video Loss Detection		Programmable			
	Alarm Relay Output		X2, Terminal Block, 1.0A / 24V (Programmable)			
Communication	Network Connectivity		Ethernet RJ-45 connector, 10/100/1000Mbps, supports DHCP/PPPoE/DDNS			
	Remote Control Software		SpecoRemote™ / CMS			
	Access Remote		8 Levels			
	Remote Operation		Monitoring, Playback, Recording, System Setup, Dome Camera Control, Remote Burn			
	RS232C		D-sub 9 pin female			
	RS485		Terminal Block			
	Dome Control Protocol		Pelco D, Pelco P, Panasonic, Panasonic C, AD422, Fastrax, JVC			
	IP Cameras		Up To 4 Channels			
IP Camera Protocols		Panasonic, Xvision, ONVIF, Lorex, AMTK, Luxon, Sanyo, Hunt, Acti, Sony, Axis 200, Vivotek 7000, Dynacolor				

For more information contact Speco Technologies 200 New Highway, Amityville, NY 11701

Toll Free: 1-800-645-5516 Fax: 631-957-9142 or 631-957-3880 Website: www.specotech.com